

## 722TC Hose

### 4-Wire Spiral Hose with SAE 100R12 Performance

#### Long Lasting Performance in Demanding Applications

722TC hose was designed with performance in mind. Resilient 4-wire spiral construction and Parker's leading Tough Cover® provide unmatched application usage. 722TC hose provides SAE 100R12 performance enabling its use in a wide variety of applications. 722TC hose is also one-half the bend radius of SAE 100R12 hose, making it easy to install and reducing the amount of hose needed.



BD/Parker Part No.	Hose ID		Hose OD		Working Pressure psi	Min. Bend Radius		Weight		Parkrimp Series		Packaging Qty.
	inch	mm	inch	mm		inch	mm	lbs/foot	kg/m	43	71	
722TC-6 722TC-6-BX	3/8	10	0.80	20	4000	2-1/2	65	0.40	,60	•		Bulk, 140' Box, 50'
722TC-8 722TC-8-BX	1/2	12,5	0.93	24	4000	3-1/2	90	0.54	,80	•		Bulk, 140' Box, 50'
PH722TC-10	5/8	16	1.06	27	4000	4	100	0.74	1,10	•		Bulk, 140'
722TC-12-RL 722TC-12-BX	3/4	19	1.21	31	4000	4-3/4	120	0.94	1,40	•		Reel, 140' Box, 50'
722TC-16-RL 722TC-16-BX	1	25	1.50	38	4000	6	150	1.34	1,99	•		Reel, 140' Box, 50'
722TC-20 722TC-20-BX	1-1/4	31,4	1.84	46	3000	8-1/4	210	1.74	2,59	•		Bulk, 140' Box, 50'
PH722TC-24 PH722TC-32	1-1/2 2	38 51	2.07 2.59	53 66	2500 2500	10 12-1/2	250 320	2.01 2.75	2,99 4,09		• •	Bulk, 100' Bulk, 100'

#### More New 43 Series Fitting Options from BD:

BD Part No.	Parker Part No.	Description	Unit
PP-00114	11543-16-16	Parker 43 Series, Code 61 Straight, -16-16	1
PP-00115	11543-20-20	Parker 43 Series, Code 61 Straight, -20-20	1
PP-00116	11543-24-20	Parker 43 Series, Code 61 Straight, -24-20	1
PP-00117	11743-24-20	Parker 43 Series, Code 61 45° Elbow, -24-20	1
PP-00118	11743-24-24	Parker 43 Series, Code 61 45° Elbow, -24-24	1
PP-00119	16A43-12-12	Parker 43 Series, Code 62 Straight, -12-12	2
PP-00120	16A43-16-16	Parker 43 Series, Code 62 Straight, -16-16	1
PP-00121	16F43-12-12	Parker 43 Series, Code 62 45° Elbow, -12-12	1
PP-00122	16N43-16-16	Parker 43 Series, Code 62 90° Elbow, -16-16	1
PP-00123	16N43-20-20	Parker 43 Series, Code 62 90° Elbow, -20-20	1
PP-00124	1J043-16-12	Parker 43 Series, Male Seal-Lok, Straight, -16-12	2

#### 722TC Hose Features

- Half the bend radius of SAE 100R12 hose
- 4-spiral construction for longer lasting hose in high impulse, heavy duty cycle applications
- SAE 100R12 performance
- -6 through -20 utilizes 43 Series fittings
- Petroleum-based hydraulic fluids
- Nitrile synthetic rubber inner tube
- Synthetic rubber cover
- -40°F to 257°F temperature range

K-1559

**1-866-GET-MROP • www.BarnesDistribution.com**

1301 East 9th Street, Suite #700, Cleveland, Ohio 44114-1824



## FLEXIBLE 722TC

Tuyau flexible à armure métallique 4 épaisseurs, performance SAE 100R12

Performance longue durée en service intensif

Le flexible 722TC est conçu en priorisant la performance. De construction résiliente à armature métallique 4 épaisseurs, avec revêtement avant-gardiste Tough Cover® de Parker, il est utilisé de façon incomparable. La performance SAE 100R12 du 722TC permet de l'utiliser dans un vaste éventail d'applications. Le 722TC a un rayon de courbure la moitié des autres flexibles SAE 100R12 ce qui facilite son installation et diminue la longueur de tuyau requise.



No de pièce BD/Parker	Flexible DI		Flexible DE		Pression de service psi	Rayon de courbure min		Poids		Séries Parkrimp		Qté emballage
	Po	mm	Po	mm		inch	mm	lb/pi	kg/m	43	71	
722TC-6 722TC-6-BX	3/8	10	0.80	20	4000	2-1/2	65	0.40	,60	•		Vrac 140' Boîte 50'
722TC-8 722TC-8-BX	1/2	12,5	0.93	24	4000	3-1/2	90	0.54	,80	•		Vrac 140' Boîte 50'
PH722TC-10	5/8	16	1.06	27	4000	4	100	0.74	1,10	•		Vrac 140'
722TC-12-RL 722TC-12-BX	3/4	19	1.21	31	4000	4-3/4	120	0.94	1,40	•		Bobine 140' Bobine 50'
722TC-16-RL 722TC-16-BX	1	25	1.50	38	4000	6	150	1.34	1,99	•		Bobine 140' Bobine 50'
722TC-20 722TC-20-BX	1-1/4	31,4	1.84	46	3000	8-1/4	210	1.74	2,59	•		Vrac 140' Boîte 50'
PH722TC-24 PH722TC-32	1-1/2 2	38 51	2.07 2.59	53 66	2500 2500	10 12-1/2	250 320	2.01 2.75	2,99 4,09		• •	Vrac 100' Vrac 100'

### Nouvelles options de raccordement Série 43 par BD :

No de pièce BD	No de pièce Parker	Description	Unités
PP-00114	11543-16-16	Parker série 43, Code 61 Droit, -16-16	1
PP-00115	11543-20-20	Parker série 43, Code 61 Droit, -20-20	1
PP-00116	11543-24-20	Parker série 43, Code 61 Droit, -24-20	1
PP-00117	11743-24-20	Parker série 43, Code 61 Coude 45°, -24-20	1
PP-00118	11743-24-24	Parker série 43, Code 61 Coude 45°, -24-24	1
PP-00119	16A43-12-12	Parker série 43, Code 62 Droit, -12-12	2
PP-00120	16A43-16-16	Parker série 43, Code 62 Droit, -16-16	1
PP-00121	16F43-12-12	Parker série 43, Code 62 Coude 45°, -12-12	1
PP-00122	16N43-16-16	Parker série 43, Code 62 Coude 90°, -16-16	1
PP-00123	16N43-20-20	Parker série 43, Code 62 Coude 90°, -20-20	1
PP-00124	1J043-16-12	Parker série 43, Seal-Lok mâle Droit, -16-12	2

### Caractéristiques du flexible 722TC

- Rayon de courbure la moitié des flexibles SAE 100R12
- Construction spiralée à 4 épaisseurs donne un flexible longue durée dans des applications à cycles de service intensif et à hautes impulsions.
- Performance SAE 100R12
- Raccords série 43, -6 pompés, -20 utiles
- Fluides hydrauliques à base de pétrole
- Tube interne en caoutchouc nitrile synthétique
- Revêtement en caoutchouc synthétique
- Échelle de températures -40°F à 257°F



1-866-GET-MROP • [www.BarnesDistribution.com](http://www.BarnesDistribution.com)

1301 East 9th Street, Suite #700, Cleveland, Ohio 44114-1824

K-1559